LUBRICATION ENGINEERS®, INC. FORT WORTH, TX 76107 300 Bailey Avenue

MATERIAL SAFETY DATA SHEET SECTION I - PRODUCT IDENTIFICATION

SUPPLIER:

Lubrication Engineers®, Inc. 300 Bailey Avenue Fort Worth, TX 76107

EMERGENCY TELEPHONE NUMBERS.: Company:

(817) 834-6321 In the event of an emergency spill, fire, or exposure—Call:

Chemtrec: (Within UŠA) (800) 424-9300 Chemtrec: (Within USA) (800) 424-9300 (Outside USA—call collect) (703) 527-3887

TRADE NAME AND SYNONYMS:

1232 ALMATEK® General Purpose Lubricant

CHEMICAL NAME AND SYNONYMS:

Not applicable

FORMULA:

Not applicable

CHEMICAL FAMILY:

Hydrocarbon

TYPICAL CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE: Red lubricant

VISCOSITY: @ 210°F, SUS

@ 100°C, cSt Not applicable

VISCOSITY: @ 100°F, SUS

Not applicable

@ 40°C, cSt

Lube oil odor

Not applicable

Not applicable

RELATIVE DENSITY:

MELTING POINT: °F

SOLUBILITY IN WATER: Negligible PH: 6-8

(Air=1) > 1

POUR POINT: °F

Not applicable

360

ODOR:

BOILING POINT: °F

FLASH POINT: °F (Method)

400 (C.O.C.)

>500

SPECIFIC GRAVITY: (H₂O=1)

VAPOR PRESSURE: (mm Hg @ 60°F) <5

Approx. 0.95

INGREDIENTS

WT PCT (APPROX) TLV

ORAL LD50

DERMAL LD50

HAZARDOUS INGREDIENTS:

Zinc compounds

Oil Mist (mineral) >80.0 Zinc diamyldithiocarbamate (oxidation inhibitor) < 1.0

5mg/m³-TWA Unknown Unknown

Print Date: September 12, 2006

Unknown

Unknown

14900 mg/kg Rat >2000 mg/kgRabbit 14900 mg/kg Rat >2000 mg/kgRabbit

NON-HAZARDOUS INGREDIENTS:

ADDITIVES AND/OR OTHER INGREDIENTS: This product is a mixture. The specific chemical identity of hazardous ingredients and non-hazardous ingredients, their C.A.S. numbers and their exact percent of composition are proprietary to Lubrication Engineers®, Inc. and are being withheld as Trade Secrets. The above listing of hazardous ingredients discloses the properties, approximate concentration and known toxicological effects of the hazardous ingredients. This material is an automotive/industrial lubricant with a low order of toxicity and irritancy. The product is formulated with ingredients that are not designated as harmful to the ozone.

REGULATORY INFORMATION:

SARA Title III: This product does not contain any chemical substance on the SARA Extremely Hazardous Substances list. If this product contains any chemicals that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372, they will be listed in the above HAZARDOUS INGREDIENTS section.

TSCA: This material is in compliance with the Toxic Substances Control Act (15 USC 2601-2629) and all components of this product appear on the Toxic Substance Control Act (TSCA) inventory list.

Clean Air Act: No ozone depleting chemicals listed in Title VI, Stratospheric Ozone Protection, Section 602 of the Clean Air Act are present or used in the manufacturing process of this product.

FIRE AND EXPLOSION HAZARD DATA

1232 ALMATEK® General Purpose Lubricant Effective Date: September 6, 2006

Page 1

FLASH POINT: °F (Method) **UEL** FLAMMABLE LIMITS: LEL 400 °F (C.O.C.) Unknown **EXTINGUISHING MEDIA:** Foam, dry chemical, water fog, or carbon dioxide SPECIAL FIRE FIGHTING PROCEDURES: Do not direct a solid stream of water into fire. Treat as a petroleum oil fire. Respiratory protection required for fire fighting personnel. UNUSUAL FIRE AND EXPLOSION HAZARDS: None **HEALTH HAZARD DATA** THRESHOLD LIMIT VALUE: (If Established) Not established. Oil mist = 5mg/m³ **EFFECTS OF OVEREXPOSURE:** Although there are no consistent primary routes of entry, the product may cause mild dermatitis upon prolonged contact and is expected to be an eye and lung irritant. Any existing skin, eye, or lung irritation may be aggravated by direct contact. No components are listed on OSHA, I.A.R.C., or N.T.P. lists for carcinogens. **EMERGENCY AND FIRST AID PROCEDURES** EYE CONTACT: Flush immediately with water until irritation subsides. SKIN CONTACT: Wash affected skin area with mild soap and water. INGESTION: Do not induce vomiting. Contact a physician. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. Contact a physician. REACTIVITY DATA STABILITY: (Thermal, Light, Etc.) CONDITIONS TO AVOID: Stable Contact with nuclear radiation and strong oxidizing materials. INCOMPATIBILITY: (Materials to avoid) Strong oxidizing materials. HAZARDOUS DECOMPOSITION PRODUCTS: Dense smoke; oxides of C, S, N and Zn; Ca compounds; hydrogen sulfide. HAZARDOUS POLYMERIZATION: Will not occur. SPILL OR LEAK PROCEDURES STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Treat as a petroleum oil spill. WASTE DISPOSAL METHOD: Incinerate where permitted under federal, state, and local laws. Used petroleum products may be recycled through re-refining processes. SPECIAL PROTECTION INFORMATION EYE PROTECTION:

Sufficient t

Sufficient to avoid direct contact.

SKIN PROTECTION:

1232 Almatek® General Purpose Lubricant Effective Date: September 6, 2006

Print Date: September 12, 2006 Page 2

There are several recognized and accepted systems that assign hazard ratings to materials. Although this product has not been evaluated specifically against these systems, the ratings for the National Fire Protection Association (NFPA) and the National Paint and Coatings Association's Hazardous Material Identification System (HMIS) are:

	NFPA	HMIS
Health	2	1
Flammability	1	1
Reactivity	1	1

Protective neoprene or plastic gloves may be desired.