

LUBRICATION ENGINEERS®, INC.
300 Bailey Avenue FORT WORTH, TX 76107

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

SUPPLIER:
Lubrication Engineers®, Inc.
300 Bailey Avenue
Fort Worth, TX 76107

EMERGENCY TELEPHONE NUMBERS.:
Company: (817) 834-6321
In the event of an emergency spill, fire, or exposure—Call:
Chemtrec: (Within USA) (800) 424-9300
(Outside USA—call collect) (703) 527-3887
TRADE NAME AND SYNONYMS:
2059 MONOLEX® Penetrating Oil (Aerosol)

CHEMICAL NAME AND SYNONYMS:
Not applicable

CHEMICAL FAMILY:
Hydrocarbon

FORMULA:
Not applicable

*****SECTION II*****

TYPICAL CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE: Amber lubricant
VISCOSITY: @ 210°F, SUS Not applicable
@ 100°C, cSt Not applicable
ODOR: Banana oil odor
VISCOSITY: @ 100°F, SUS Not applicable
@ 40°C, cSt Not applicable
RELATIVE DENSITY: (Air=1) >1
SOLUBILITY IN WATER: Negligible
PH: 6-8
MELTING POINT: °F Not applicable
POUR POINT: °F Not applicable
BOILING POINT: °F Unknown
FLASH POINT: °F (Method) 120 (TCC)
VAPOR PRESSURE: Unknown
SPECIFIC GRAVITY: (H₂O=1) <1.0

FLAMMABILITY CATEGORY PER 16 CFR 1500.45:
Extremely flammable

*****SECTION III*****

INGREDIENTS

	WT PCT (APPROX)	TLV	ORAL LD50	DERMAL LD50
HAZARDOUS INGREDIENTS:				
Oil Mist (mineral)	>90.0	5mg/m ³ -TWA	Unknown	Unknown
Acetic acid, pentyl ester (amyl acetate)	1.0-3.0	100 ppm-TWA	6500 mg/kg Rat	Unknown
1,2,4-Trimethylbenzene	<0.25	25 ppm-TWA	Unknown	Unknown
Kerosene	>5.0	100mg/m ³ -TWA	20gm/kg gpg	Unknown
Xylene	<0.60	100 ppm-TWA	4300 mg/kg Rat	Unknown
Carbon dioxide	1.5-3.5	800 ppm	Unknown	Unknown

NON-HAZARDOUS INGREDIENTS:

ADDITIVES AND/OR OTHER INGREDIENTS: This product is a mixture. The specific chemical identity of hazardous ingredients and non-hazardous ingredients, their C.A.S. numbers and their exact percent of composition are proprietary to Lubrication Engineers®, Inc. and are being withheld as Trade Secrets. The above listing of hazardous ingredients discloses the properties, approximate concentration and known toxicological effects of the hazardous ingredients. This material is an automotive/industrial lubricant with a low order of toxicity and irritancy. The product is formulated with ingredients that are not designated as harmful to the ozone.

REGULATORY INFORMATION:

SARA Title III: This product does not contain any chemical substance on the SARA Extremely Hazardous Substances list. If this product contains any chemicals that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372, they will be listed in the above HAZARDOUS INGREDIENTS section.

TSCA: This material is in compliance with the Toxic Substances Control Act (15 USC 2601-2629) and all components of this product appear on the Toxic Substance Control Act (TSCA) inventory list.

Clean Air Act: No ozone depleting chemicals listed in Title VI, Stratospheric Ozone Protection, Section 602 of the Clean Air Act are present or used in the manufacturing process of this product.

Used petroleum products may be recycled through re-refining processes.

*****SECTION IX*****

SPECIAL PROTECTION INFORMATION

EYE PROTECTION:

Sufficient to avoid direct contact.

SKIN PROTECTION:

Protective neoprene or plastic gloves may be desired.

RESPIRATORY PROTECTION:

Usually not needed in open, unconfined areas. If TLV is exceeded wear NIOSH approved self-contained breathing device or respirator.

VENTILATION:

Usually not needed in open, unconfined areas. In enclosed areas, sufficient ventilation to meet recommended TLV of 100 ppm. Ventilation is necessary at floor level as vapors are heavier than air.

OTHER:

Usually not needed.

*****SECTION X*****

SPECIAL PRECAUTIONS

Do not store above 120 °F. Keep away from heat, sparks, open flames, and strong oxidants. Avoid eye contact and prolonged skin contact. Avoid breathing oil mists. Wash thoroughly after handling.

*****SECTION XI*****

HAZARD RATINGS

There are several recognized and accepted systems that assign hazard ratings to materials. Although this product has not been evaluated specifically against these systems, the ratings for the National Fire Protection Association (NFPA) and the National Paint and Coatings Association's Hazardous Material Identification System (HMIS) for the lubricant residue and as applied are:

	NFPA	HMIS
Health	2	2
Flammability	4	4
Reactivity	0	0